





# **SF-150HX**

## 多功能电脑切带机(转角)

### Bevel Cutter)

功能特性 高速:每分钟可切断 80 — 100 片(以 100mm 长度为例 )。 高精度:每一次切断都由步进电机监控,以保证每次操作的高精确性。光 电感应强可上确定位商标、精确如在商标识即截上。 转角功能、只要输入长度、宽度、角度等参数、电脑将自动切出你所需的如: 菱形、平行四边形、方形、宝塔形等各种形状 冲孔装置:根据用户需要,可冲不同大小直径的孔。 切断面进行高温热封厚,且对于整充无列、不散丝。 的耐面进行温热封厚,且对于整充无列、不散丝。 自动操作;只需设定您所需的如:切断长度、数量、角度等参数。其余工作 申脑自动完成


电脑自动完成

记顾自幼儿说应 破障自检: 切刀座、无材料、色标传感器、转刀座一旦出现故 动在屏幕上显示。 自动暂停- 一旦材料用完,系统将自动停止工作。 记忆功能: 在开关关闭前,自动储存当前所设置的所有参数。 

### 可切断材质

各种编织带魔术贴、鞋带、商标等各种尼龙材质。

Special features





Special Teatures.

High speed; It can out 80-100 pcs per minute (e.p. 100 mm long)

Accuracy: Cut-length is accurate owing to a stepping motor A sensor makes

out-length accurate by automatic sensing at set-position.

Multi-Angle: By use of multi-angle out fuction of straight knife, it can cut many shapes

Multi-Angle: By use of multi-angle cut fuction of straight kinler, it can cut many snapes as parallelogram/hombic, trapead, etc by only set the length quantify, angle. Punching Device: According to the needs of user, it can punching different size of the diameter of the holes. Cutting Type: The blade is made of high quality steel. Hot cutter can cutting ribbon, thin woven belt and the hot knife melts the end of the tape, cutting is sealed neatly,

smoothly without fraying.

Automatic operation: It works automatically only by setting length, quantity and angle Automatic operation I whose automatically in yet yet early regard yet and in a first Computerised. Automatic work, stop. The special fault by self-diagnosis, direct show the fault problem on the screen, it will easy for you to find dear way to repair. Automatic slopper: It stops automatically if materials run out during operation. Memory, Self-eingth, set quantity & set speed are not erased even if power off&on.

All kinds of woven belt, velcro, shoelace, plastic soft tube, computer cable, label etc

| 型 号      | 切断长度(mm)       | 最大切断宽度 直角/斜角 (mm)  | 最大收料高度(mm)           | 100mm切断速度 <sub>(p/min)</sub> | 刀片最高温度(で)       | 建议气压 (Mpa)           | 电压(v)   | 冲孔直径(mm)          | 功率 (Kw) | 重 量 <sub>(kg)</sub> | 包装尺寸LWH (mm) |
|----------|----------------|--------------------|----------------------|------------------------------|-----------------|----------------------|---------|-------------------|---------|---------------------|--------------|
| Model    | Cutting Length | Max. Cutting Width | Max. Receipts Height | Cutting Speed                | Max. Blade Temp | Recommended Pressure | Voltage | Punching Diameter | Power   | Weight              | Package Size |
| SF-150HX | 20-99999       | 100/35             | -                    | 120                          | 420             | 20~50                | 220     | 2-5               | 0.5     | 77.5                | 800x570x615  |



# SF-150H

## 多功能电脑切带机(热刀)

### Hot Cutter)

高速: 每分钟可切断 50 — 100 片(以 100mm 长度为例、带收料装置) 高速: 每分钟可切断 50 — 100 片(以 100mm 长度为例,带收料装置)。高精度: 每一次切断都由步进电机监控,以保证每次操作的高精确性。光电感应器可准确定位商标,精确切在商标切断线上。收料功能: 根据设定收料数量,机器自动叠料,方便用户捆扎。冲孔装置: 根据用两需要,可冲不同大小直径的孔切断面平整,刀刃采用优质钢材制成,热刀可对彩色丝带、轻薄编织带的切断面进行高温热封厚、且封口平整无毛刺,不散丝。

由切无成。 故障自检:切刀座、无材料、色标传感器、转刀座一旦出现故障,系统将自

动在屏幕上显示 切在屏幕上显示。 自动暂停:一旦材料用完,系统将自动停止工作。 记忆功能:在开关关闭前,自动储存当前所设置的所有参数。

### 可切断材质

各种编织带魔术贴、鞋带、商标等各种尼龙材质。

Special readures. High spect it can cut 50-100 pcs per minute (e.p. 100 mm long, it include collecting device) Accuracy: Cut-length is accurate owing to a stepping motor. A sensor makes cut-length accurate by automatic sensing at set-position. Collecting Function: Setting the quantity, it will be collecting automatically, so that clients can be easily packed. Punching Device: Accrding to the needs of user, it can punching different size of the disease of the Miss.

diameter of the holes.

claimeter of the noies.

Cutting Type: The blade is made of high quality steel. Hot cutter can cutting ribbon, thin woven belt and the hot knife melts the end of the tape, cutting is sealed neatly, smoothly

woven belt and the hot knifle melts the end of the tape, cutting is sealed neatily, smoornly without fraving.

Automatic operation: It works automatically only by setting length and quantity.

Computerised: Automatic work stop. The special fault by setf-diagnosis direct show the fault problem on the screen at will easy for you to find clear way to repair.

Automatic stopper: It stops automatically if materials run out during operation. Memory: Set-length, set quantity&set speed are not erased even if power off&on.

Apllication
All kinds of woven belt, velcro, shoelace, plastic soft tube, computer cable, label etc.

| 型 号     | 切断长度(mm)       | 最大切断宽度 直角/斜角 (mm)  | 最大收料高度 <sub>(mm)</sub> | 100mm切断速度 (p/min) | 刀片最高温度(%)       | 建议气压 (Mpa)           | 电压(v)   | 冲孔直径(mm)          | 功率 (Kw) | 重 量 <sub>(kg)</sub> | 包装尺寸LW.H(mm) |
|---------|----------------|--------------------|------------------------|-------------------|-----------------|----------------------|---------|-------------------|---------|---------------------|--------------|
| Model   | Cutting Length | Max. Cutting Width | Max. Receipts Height   | Cutting Speed     | Max. Blade Temp | Recommended Pressure | Voltage | Punching Diameter | Power   | Weight              | Package Size |
| SF-150H | 20-99999       | 100                | 30                     | 100/50            | 420             | 20~50                | 220     | 2-5               | 0.65    | 77.5                | 800x570x615  |



\_\_\_\_\_\_

# **SF-150LR**

## 多功能电脑切带机(冷、热)

Auto-cutting Machine(Multi-function,

### Cold &Hot Cutter)

### 功能特性

切底中区 高速:每分钟可切断 50 — 100 片(以 100mm 长度为例,带收料装置)。 高精度:每一次切断都由步进电机监控,以保证每次操作的高精确性。 光电感应器可准确定位商标,精确切在商标切断线上。

切断順十登: 刀刃木用讥讽物物制成。然刀刃科形已至时、轻励端系形的切断面进行高温热封厚、且封口平整无毛刺、不散丝,但对厚料效果不佳。 自动操作: 只需设定您所需的如: 切断长度、数量、等参数。其余工作电

目切珠(F: 八高) 以上记引 而时知,勿如下风、如至、守少或。宋八二下之 脑自动完成。 故障自检: 切刀座、无材料、色标传感器、转刀座一旦出现故障,系统将 自动在屏幕上显示。

工业小。 一旦材料用完,系统将自动停止工作。 自动暂停. 记忆功能: 在开关关闭前,自动储存当前所设置的所有参数。

各种编织带魔术贴、鞋带、商标等各种尼龙材质。







High speed: It can cut 50-100 pcs per minute.(e.p. 100 mm long,it include collecting device)

Accuracy: Cut-length is accurate owing to a stepping motor. A sensor makes cut-length accurate by automatic sensing at set -position

cut-length accurate by automatic sensing at set-position.

Collecting Function:Setting the quantity, it will be collecting automatically, so that clients can be easily packed.

Punching Device: According to the needs of user, it can punching different size of the diameter of the holes.

Cutting type: The kindle is made of high quality steet. Hot cutter can cutting ribbon, thin woven belt and the hot kinfer melts the end of the tape, cutting is sealed neatly, smoothly without fraying, but except the thick materials.

Automatic operation: It works automatically only by setting length and quantity.

Computerised: Automatic work, stop. The special fault by self-diagnosis direct show the fault problem on the screen; thy ill easy for you find clear way for repair Automatic stopper. It stops automatically if materials run out during operation.

Memory: Set-length, set quantity&set speed are not erased even if power off&on.

All kinds of woven belt, velcro, shoelace, plastic soft tube, computer cable, label etc.

|          |                |                    |                        |                              |                 | Y                    |         |                      |         |                     |              |
|----------|----------------|--------------------|------------------------|------------------------------|-----------------|----------------------|---------|----------------------|---------|---------------------|--------------|
| 型 믁      | 切断长度(mm)       | 最大切断宽度 直角/斜角 (mm)  | 最大收料高度 <sub>(mm)</sub> | 100mm切断速度 <sub>(p/min)</sub> | 刀片最高温度(で)       | 建议气压 (Mpa)           | 电压(v)   | 冲孔直径 <sub>(mm)</sub> | 功率 (Kw) | 重 量 <sub>(kg)</sub> | 包装尺寸LWH (mm) |
| Model    | Cutting Length | Max. Cutting Width | Max. Receipts Height   | Cutting Speed                | Max. Blade Temp | Recommended Pressure | Voltage | Punching Diameter    | Power   | Weight              | Package Size |
| SF-150LR | 20-99999       | 100                | 40                     | 100/50                       | 250             | 20~50                | 220     | 2-5                  | 0.65    | 77.5                | 800x570x615  |