



# SF-120HL

## 电脑切带机(冷刀红外)

Label Cold Knife Cutter

## 功能特性

高速:每分钟可切断 100-120 片。(以 50mm 长度为例) 高精度:光电感应器可准确的捕捉商标的切断线,从而精确的控 制每次的有效切断长度。

切断面平整:刀刃由优质进口钢材制成,保证了断面的平整性。 自动操作:只需设定您所需的切断长度和数量,其余工作都自动 完成

自动暂停: 一旦材料用完,将自动停止工作。

记忆功能:在开关关闭前,自动存储所设值的切断长度和切断数 量以及切断速度。

#### 可切断材质

商标、编织带、魔术贴、塑料软管、鞋带、塑料拉链、电脑排线。





### Special features:

High speed: It can cut 100~120 pcs per minute.(50 mm long) Accuracy: Cut-length is accurate owing to a stepping motor Cutting type: Cutting is neat due to using a cold cutter which is durable because they are made of high-speed steel.

Automatic operation: It works automatically only by setting length and quantity.

Automatic stopper: It stops automatically if materials run out during operation.

Memory: Set-length, set-q'ty & set-speed are not erased even if power off & on.

### Apllication

Woven label, printed label, ribbon tape, bag band, etc.

型 号	切断长度(mm)	最大切断宽度(mm)	切断速度 <sub>(p/min)</sub>	电压 (v)	频率 (Hz)	额定功率(kw)	包装尺寸LWH(mm)	重量(kg)	装箱率(台)
Model	Cutting Length	Max. Cutting Width	Cutting Speed	Voltage	Frequency	Power	Package Size	Weight	Loading Rate Pic
SF-120HL	1-99999	105	120	110/220	50/60	0.66	410x525x430	24/29	1



# SF-120HLR

## 电脑切带机(冷、热红外)

Lable Cutter (cold &hot)

## 功能特性

高速:每分钟可切断 100 片左右。(以 50mm 长度为例)

高精度:光电感应器可准确的捕捉商标的切断线,从而精确的控制每次的有效切断长度。 切断面平整:热刀可对彩色丝带、轻薄编织带的切断面进行热封,

且封口平整无毛边,但对厚料效果不佳。刀刃由进口优质钢材制成,使用寿命长。

自动操作: 只需设定您所需的切断长度和数量, 其余工作都自动 完成。

自动暂停:一旦材料用完,将自动停止工作。

记忆功能: 在开关关闭前,自动存储所设值的切断长度和切断数量以及切断速度。

## 可切断材质

尼龙商标、织带、彩色缎带、背包带等尼龙材质。



#### Special features:

High speed: It can cut 100 pcs per minute. (50 mm long)
Accuracy: Cut-length is accurate owing to a stepping motor
Cutting type: Melting & cutting by hot knife, label is cut neatly
without fraying but not for heavy materials and installed with

PURE 梅花 Mei Hua

anti-static electricity device.

Automatic operation: It works automatically only by setting length and quantity

Automatic stopper: It stops automatically if materials run out during operation.

Memory: Set-length, set-q'ty & set-speed are not erased even if power off & on.

## Apllication

Woven label, printed label, ribbon tape, bag band, etc.

型 号	切断长度(mm)	最大切断宽度(mm)	切断速度(p/min)	刀片最高温度(%)	电压(v)	频率 (Hz)	额定功率(kw)	包装尺寸LW.H(mm)	重量 (kg)	装箱率(台)
Model	Cutting Length	Max. Cutting Width	Cutting Speed	Max. Blade Temp	Voltage	Frequency	Power	Package Size	Weight	Loading Rate Pic
SF-120HLR	1-99999	95	90	250	110/220	50/60	0.66	410x525x430	24/29	1

# SF-120H/300M

# 电脑切带机(热刀)配送带装置

Hot Knife Cutter With Auto-feeder



## 功能特性

高速:每分钟可切断 100~120 片。(以 50mm 长度为例) 高精度:每一次切断都由步进电动机监控,以保证每次操作的高 精确性。

切断面平整: 热刀可对彩色丝带、轻薄编织带的切断面进行高温 热封,且封口平整无毛边,刀刃由进口优质钢材制成,使用寿命长。 自动操作,只需设定您所需的切断长度和数量,其余工作都自动完成。 自动暂停: 一旦材料用完,将自动停止工作。

记忆功能:在开关关闭前,自动存储所设值的切断长度和切断数量以及切速度。

送带装置:采用红外传感控制,根据主机的工作速度自动调节送 带速度,预放转送橡筋,使其保持统一的张力,可确保切断长度的 准确性。

可切断材质

松紧带、编织带、尼龙织带、彩色缎带、背包带等尼龙材质。

## Special features:

High speed: It can cut 100~120 pcs per minute. (50 mm long) Accuracy: Cut-length is accurate owing to a stepping motor.

Cutting type: Melting & cutting by hot knife, tapes are cut neatly without fraying and installed with anti-static electricity device.

Automatic operation: It works automatically only by setting length

and quantity.

Automatic stopper: It stops automatically if materials run out during

operation.

Memory: Set-length, set-q'ty & set-speed are not erased even if power off & on.

power off & on.
Auto-feeding machine: for multi-purpose pre-feeding, especially for heavier and elastic material, it is applicable for 120series auto-cutting machine. Pre-feeding device to keep a constant

## tension of elastic band for correct length. Application

Woven tapesstrip tapes, ribbon tape, bag band, webbing, etc.

型 号	送带速度 <sub>(mm)</sub>	最大切断宽度(mm)	电机转度 <sub>(r/min)</sub>	电压 (v)	频率 (Hz)	额定功率(kw)	包装尺寸LW.H (mm)	装箱率(台)
Model	Feeding Speed	Feeding Width	Motor Speed	Voltage	Frequency	Power	Package Size	Loading Rate Pic
SF-120H/300M	自动	140	1500	110/220	50/60	0.06	410x525x430	1